



<u>FLEXIBLE</u>

windows are built to

your individual needs

"You'll appreciate the quality we build into every window!"











• Fusion Welded Frame and Sash VERSATILE &

Welding creates a fully sealed, continuous profile that eliminates potential air and water penetration through frame and sash corners.

· Maintenance Free Solid uPVC Vinyl Profiles

The multi-chambered design provides structural strength as well as insulating air pockets which reduce heat and cold transfer.

Integral Pull Rail


Permits single sash to be operated with ease.

· Built-in Water Management Systems

Carefully engineered independent water management system allows for quick drainage to the exterior.

· Integral Brick Mould with Nail Fin

Ideal for brick and siding applications, offering cleaner details and improved performance (301BMJ only).



Window Ratings AAMA/WDMA/CSA101/LS.2/A440-08&11 CSA A440 S1-09 R-PG25

Water Penetration Resistance w/ screen 220pa no screen 180pa A3 Grade 10

no screen 180pa As Grade 10
Energy Rating: +33* • U Value: 0.28(1.59)*
Energy Rating: +41 • U Value: 0.18(1.02)*
(Triple glazed with Low E and Krypton Gas and a warm edge spacer)
CSA Certified • NFRC Certified
Energy Star® Qualified • Window Wise Certified
USA ENERGY STAR U.29 SHGC .56

Single Tilt Slider

Style 301VS/301BMJ

Width: Min 18" Height: Min 12" Max 50"

Note: If Height is between 12" and 13", width can be no less than 22"

Double End Vent

Style 301VSEV/301BMJEV

Height: Min 12" Max 50"

Width: Min 42" Height: Min 12"

* Tested with Low E. Argon Gas and a warm edge spacer * Ask your dealer f

alass







Double Bond Glazing System

Flexible dual durometer seals hug the sash glass from both sides. The system also includes a glazing tape applied to the interior side. The result is an unprecedented barrier against air and water penetration.

Commercial Glazing Technique

Exterior glass stops, combined with the Double Bond Glazing, are more effective in maintaining a well-sealed window.

· High Performance Glass Options

Choose Solar Gain Low E for free solar heat or Solar Shield Low E for reducing solar heat gain. Argon and Krypton Gas fillings will maximize heat savings! KeepSafe Glass is the laminate of choice for security, quiet and safety! E-Clean Glass uses the energy of the sun to reduce dirt on your glass.

7/8" Overall Insulating Glass

Results in superior thermal performance. Our optional high performance triple glass has two 1/4" air spaces. With Krypton Gas and double Solar Shield Low E, this results in a R8.2 (.12U) center glass value.

Warm Edge Spacer Technology

Only the best warm edge spacers will reduce perimeter condensation on an insulating glass unit, fight mold and increase the comfort of your home.

IGMA Approved

Certification Numbers - Stainless #2521-P, TempSmartTM 2248





Triple Seal

Three layers of premium Fin Seal stop air and water as they reduce sound transmission. Benefit from the best sliding seals available!

Double Neoprene Bulbs

Compression style seals close tight where the sash meets the frame and sliding is not required. Our engineers insisted that you get this premium component!

Recessed Tilt Latches

Your operating sash tilts in for easy cleaning from inside your home. Our recessed design maintains a clean and attractive sight line in your window.

Cam Locks

Heavy duty 180 degree locking cams pull your operating sash and frame tightly together for a great seal!

Smart Lock (Optional)

Smart Locks allow you to both unlock and tilt your sash with a single operation.

Quick Lock Shoes

When you tilt your sash for cleaning, a secure locking action from multi-directional shoe expansion break-points secures the sash in place.

Hinged Drain Covers

Designed to keep bugs out while allowing water to flow to the













Optional Internal grills for beauty and distinction.











Authorized Distributor















